DesignLights Consortium





Classification	Premium
Primary Use	Outdoor Non-Cutoff and Semi-Cutoff Wall-Mounted Area Luminaires
Reported Input Wattage	40.3 W
Reported Light Output	5510 lm
Reported CCT	5000 K
Reported CRI (Ra)	82
Product ID	S-B5SFRK
DLC Family Code	XXXEXM
Listing Status	Listed
Date Qualified	2023-06-13

PRODUCT INFORMATION VIEW DETAILS

Overliffe at Date dover Liet	Octid Otata Limbia a
Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-B5SFRK
Manufacturer	BIG SHINE LED
Brand	Big Shine LED
Model Number	BSL-WP40-ALI-GNGN-5000K-120
Parent	No
Classification	Premium
DLC Family Code	XXXEXM
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires		
General Application	Mid Output		
Primary Use Designation	Outdoor Non-Cutoff and Semi-Cutoff Wall-Mounted Area Luminaires		

PRODUCT CAPABILITIES VIEW DETAILS

Integral Controls	Yes
-------------------	-----

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Panartad Light Output	5510 lm
Reported Light Output	3310 1111
Reported Efficacy (AC)	136.8 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	82
Reported R9	4
Reported IES Rf	83
Reported IES Rg	98
Reported IES Rcs,h1	-12
Reported Default Light Output	5510 lm
Reported BUG Rating	B2 U3 G1

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	40.3 W
Reported Total Harmonic Distortion	19.2 %
Reported Power Factor	0.93
Reported Default Input Wattage	40.3 W
Voltage Range	100-277 V

VERSION HISTORY VIEW DETAILS

2023-06-13	Listed	5.1	Premium