# **DesignLights Consortium**





Classification	Premium
Primary Use	Stairwell and Passageway Luminaires
Reported Input Wattage	29 W
Reported Light Output	3595.1 lm
Reported CCT	3000 K
Reported CRI (Ra)	83
Product ID	S-Y9MUL3
DLC Family Code	NNNPOZ
Listing Status	Listed
Date Qualified	2023-03-27

## **PRODUCT INFORMATION VIEW DETAILS**

Qualified Product List	Solid State Lighting		
Technical Requirements Version	5.1		
Product ID	S-Y9MUL3		
Manufacturer	BIG SHINE LED		
Brand	BIG SHINE LED		
Model Number	BSL-SW30-AM2-YGSN-[3000,3500,4000,5000]K-120		
Parent	Yes		
Classification	Premium		
DLC Family Code	NNNPOZ		
Input Power Type	AC		

#### PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires	
General Application	Low Output	
Primary Use Designation	Stairwell and Passageway Luminaires	

## **PRODUCT CAPABILITIES VIEW DETAILS**

Integral Controls	Yes
-------------------	-----

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	Occupancy Sensing
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

#### REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	3595.1 lm
Reported Efficacy (AC)	123.8 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	83
Reported R9	9
Reported IES Rf	85
Reported IES Rg	96
Reported IES Rcs,h1	-11
Reported Minimum Light Output	1184 lm
Reported Maximum Light Output	3930 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	3595.1 lm
Reported BUG Rating	B1 U3 G1

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	29 W
Reported Total Harmonic Distortion	11.1 %
Reported Power Factor	0.98
Reported Minimum Input Wattage	9.3 W
Reported Maximum Input Wattage	29
Reported Default Input Wattage	29 W
Voltage Range	100-347 V

# **TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS**

Tested Light Output	3595 lm
---------------------	---------

Tested Efficacy (AC)	123.8 lm/W
Tested CCT	2984 K
Tested CRI (Ra)	83
Tested R9	9
Tested IES Rf	85
Tested IES Rg	96
Tested IES Rcs,h1	-11 %
Tested Duv	-0.0011
Tested Backlight (TM-15 BUG)	1
Tested BUG Rating	B1 U3 G1

# **TESTED ELECTRICAL PERFORMANCE VIEW DETAILS**

Tested Voltage	120
Tested Input Wattage	29 W
Tested Total Harmonic Distortion	11.1 %
Tested Power Factor	0.977

## **VERSION HISTORY VIEW DETAILS**

2023-03-27		Listed	5.1	Premium
------------	--	--------	-----	---------