DesignLights Consortium





Classification	Premium
Primary Use	Stairwell and Passageway Luminaires
Reported Input Wattage	40.5 W
Reported Light Output	5073.1 lm
Reported CCT	3000 K
Reported CRI (Ra)	84
Product ID	S-OTGU0C
DLC Family Code	NNNPPA
Listing Status	Listed
Date Qualified	2023-03-27

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-OTGU0C
Manufacturer	BIG SHINE LED
Brand	BIG SHINE LED
Model Number	BSL-SW40-AI4-YGSN-[3000,3500,4000,5000]K-120
Parent	No
Classification	Premium
DLC Family Code	NNNPPA
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires	
General Application	Mid Output	
Primary Use Designation	Stairwell and Passageway Luminaires	

PRODUCT CAPABILITIES VIEW DETAILS

Integral Controls	Yes
-------------------	-----

Dimming Capability and Range	Continuous Dimming to 10% or below		
Integral Control Capability	No Control Capability		
Sensor Type	Daylight Sensing,Occupancy Sensing		
SSL V5 Wired Communication Protocol	0-10V Analog		
SSL V5 Wireless Communication Protocol	No Wireless Protocol		
Field Adjustable Light Output	Yes		
White-Tunable	Yes		
Warm-Dimming	No		
Field Adjustable Light Distribution	No		

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	5073.1 lm
Reported Efficacy (AC)	125.2 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	84
Reported R9	13
Reported IES Rf	85
Reported IES Rg	97
Reported IES Rcs,h1	-11
Reported Minimum Light Output	1500 lm
Reported Maximum Light Output	5073 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	5073.1 lm
Reported BUG Rating	B2 U3 G2

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	40.5 W
Reported Total Harmonic Distortion	11.7 %
Reported Power Factor	0.95
Reported Minimum Input Wattage	11.6 W
Reported Maximum Input Wattage	40.5
Reported Default Input Wattage	40.5 W
Voltage Range	100-347 V

VERSION HISTORY VIEW DETAILS

2023-03-27	Listed	5.1	Premium