DesignLights Consortium





Classification	Premium
Primary Use	Parking Garage Luminaires
Reported Input Wattage	77 W
Reported Light Output	10570 lm
Reported CCT	5000 K
Reported CRI (Ra)	82
Product ID	S-06G9A5
DLC Family Code	XXXEXL
Listing Status	Listed
Date Qualified	2023-06-13

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-06G9A5
Manufacturer	BIG SHINE LED
Brand	Big Shine LED
Model Number	BSL-CP80-CRN-SSLL-5000K-165
Parent	No
Classification	Premium
DLC Family Code	XXXEXL
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires	
General Application	High Output	
Primary Use Designation	Parking Garage Luminaires	

PRODUCT CAPABILITIES VIEW DETAILS

Integral Controls	Yes
-------------------	-----

Dimming Capability and Range	Continuous Dimming above 10%		
Integral Control Capability	No Control Capability		
Sensor Type	Occupancy Sensing		
SSL V5 Wired Communication Protocol	0-10V Analog		
SSL V5 Wireless Communication Protocol	No Wireless Protocol		
Field Adjustable Light Output	No		
White-Tunable	No		
Warm-Dimming	No		
Field Adjustable Light Distribution	No		

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	10570 lm
Reported Efficacy (AC)	137.4 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	82
Reported R9	5
Reported IES Rf	83
Reported IES Rg	98
Reported IES Rcs,h1	-11
Reported Default Light Output	10570 lm
Reported BUG Rating	B3 U3 G4

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	77 W
Reported Total Harmonic Distortion	10.8 %
Reported Power Factor	0.94
Reported Default Input Wattage	77 W
Voltage Range	100-277 V

VERSION HISTORY VIEW DETAILS

2023-06-13	Listed	5.1	Premium