DesignLights Consortium





Classification	Premium	
Primary Use	Outdoor Pole/Arm-Mounted Area and Roadway Luminaires	
Reported Input Wattage	75 W	
Reported Light Output	10050 lm	
Reported CCT	3000 K	
Reported CRI (Ra)	70	
Product ID	S-AG6ZN2	
DLC Family Code	UUUVGA	
Listing Status	Listed	
Date Qualified	2023-03-03	

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting	
Technical Requirements Version	5.1	
Product ID	S-AG6ZN2	
Manufacturer	BIG SHINE LED	
Brand	Big Shine LED	
Model Number	BSL-FL75-PD7-SNLL-CCT03-7HX6V	
Parent	Yes	
Classification	Premium	
DLC Family Code	UUUVGA	
Input Power Type	AC	

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires	
General Application	High Output	
Primary Use Designation	Outdoor Pole/Arm-Mounted Area and Roadway Luminaires	

PRODUCT CAPABILITIES VIEW DETAILS

1 of 3 3/8/2023, 8:53 PM

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	No Wired Communication Protocol
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	10050 lm
Reported Efficacy (AC)	134 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	70
Reported R9	-30
Reported IES Rf	71
Reported IES Rg	96
Reported IES Rcs,h1	-18
Reported Minimum Light Output	2948 lm
Reported Maximum Light Output	10050 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	10050 lm
Reported BUG Rating	B3 U2 G1

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	75 W
Reported Total Harmonic Distortion	10 %
Reported Power Factor	0.95
Reported Minimum Input Wattage	22 W
Reported Maximum Input Wattage	75
Reported Default Input Wattage	75 W
Voltage Range	100-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

2 of 3 3/8/2023, 8:53 PM

Tested Light Output	10164 lm
Tested Efficacy (AC)	134 lm/W
Tested CCT	3036 K
Tested CRI (Ra)	71
Tested R9	-30
Tested IES Rf	71
Tested IES Rg	97
Tested IES Rcs,h1	-16 %
Tested Duv	0.00163
Tested Backlight (TM-15 BUG)	3
Tested BUG Rating	B3 U2 G1

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Voltage	120
Tested Input Wattage	75.8 W
Tested Total Harmonic Distortion	12.4 %
Tested Power Factor	0.929

VERSION HISTORY VIEW DETAILS

2023-03-03	Listed	5.1	Premium
2023-03-02	Listed	5.1	Standard

3 of 3