DesignLights Consortium



Firefox



Classification	Premium
Primary Use	Outdoor Pole/Arm-Mounted Area and Roadway Luminaires
Reported Input Wattage	30 W
Reported Light Output	4702 lm
Reported CCT	5000 K
Reported CRI (Ra)	70
Product ID	S-YBF56A
DLC Family Code	UUUVFT
Listing Status	Listed
Date Qualified	2023-03-03

PRODUCT INFORMATION VIEW DETAILS

Solid State Lighting		
5.1		
S-YBF56A		
BIG SHINE LED		
Big Shine LED		
BSL-AL30-SX7-PHSL-5000K-III		
No		
Premium		
UUUVFT		
AC		

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires	
General Application	Low Output	
Primary Use Designation	Outdoor Pole/Arm-Mounted Area and Roadway Luminaires	

PRODUCT CAPABILITIES VIEW DETAILS

Integral Controls	Yes		
Dimming Capability and Range	Continuous Dimming to 10% or below		
Integral Control Capability	No Control Capability		
Sensor Type	Exterior Photocell,Occupancy Sensing		
SSL V5 Wired Communication Protocol	0-10V Analog		
SSL V5 Wireless Communication Protocol	No Wireless Protocol		
Field Adjustable Light Output	No		
White-Tunable	No		
Warm-Dimming	No		
Field Adjustable Light Distribution	No		

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	4702 lm
Reported Efficacy (AC)	156.7 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	70
Reported R9	-30
Reported IES Rf	73
Reported IES Rg	93
Reported IES Rcs,h1	-17
Reported Default Light Output	4702 lm
Reported BUG Rating	B1 U1 G1

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	30 W
Reported Total Harmonic Distortion	10 %
Reported Power Factor	0.95
Reported Default Input Wattage	30 W
Voltage Range	100-277 V

VERSION HISTORY VIEW DETAILS

2023-03-03	Listed	5.1	Premium
2023-03-02	Listed	5.1	Standard