# **DesignLights Consortium**





| Classification         | Premium  |
|------------------------|--|
| Primary Use            | Outdoor Pole/Arm-Mounted Area and Roadway Luminaires |
| Reported Input Wattage | 300 W  |
| Reported Light Output  | 47937 lm   |
| Reported CCT           | 4000 K   |
| Reported CRI (Ra)      | 70   |
| Product ID             | S-FZYTN9   |
| DLC Family Code        | UUUVGD   |
| Listing Status         | Listed   |
| Date Qualified         | 2023-03-03   |

### **PRODUCT INFORMATION VIEW DETAILS**

| Qualified Product List         | Solid State Lighting         |  |  |
|--------------------------------|------------------------------|--|--|
| Technical Requirements Version | 5.1                          |  |  |
| Product ID                     | S-FZYTN9                     |  |  |
| Manufacturer                   | BIG SHINE LED                |  |  |
| Brand                          | Big Shine LED                |  |  |
| Model Number                   | BSL-AL300-SX7-PHSL-4000K-III |  |  |
| Parent                         | No                           |  |  |
| Classification                 | Premium                      |  |  |
| DLC Family Code                | UUUVGD                       |  |  |
| Input Power Type               | AC                           |  |  |

## **PRODUCT CATEGORIZATION VIEW DETAILS**

| Category                | Outdoor Luminaires                                   |  |
|-------------------------|--|--|
| General Application     | Very High Output                                     |  |
| Primary Use Designation | Outdoor Pole/Arm-Mounted Area and Roadway Luminaires |  |

#### PRODUCT CAPABILITIES VIEW DETAILS

1 of 2 3/8/2023, 8:34 PM

| Integral Controls                      | No                                 |  |  |
|--|------------------------------------|--|--|
| Dimming Capability and Range           | Continuous Dimming to 10% or below |  |  |
| Integral Control Capability            | No Control Capability              |  |  |
| Sensor Type                            | No Sensor                          |  |  |
| SSL V5 Wired Communication Protocol    | No Wired Communication Protocol    |  |  |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol               |  |  |
| Field Adjustable Light Output          | No                                 |  |  |
| White-Tunable                          | No                                 |  |  |
| Warm-Dimming                           | No                                 |  |  |
| Field Adjustable Light Distribution    | No                                 |  |  |

#### REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output         | 47937 lm   |
|-------------------------------|------------|
| Reported Efficacy (AC)        | 159.8 lm/W |
| Reported CCT                  | 4000 K     |
| Reported CRI (Ra)             | 70         |
| Reported R9                   | -33        |
| Reported IES Rf               | 73         |
| Reported IES Rg               | 94         |
| Reported IES Rcs,h1           | -17        |
| Reported Default Light Output | 47937 lm   |
| Reported BUG Rating           | B4 U2 G4   |

#### REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage             | 300 W     |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 15 %      |
| Reported Power Factor              | 0.95      |
| Reported Default Input Wattage     | 300 W     |
| Voltage Range                      | 100-277 V |

## **VERSION HISTORY VIEW DETAILS**

| 2023-03-03 | Listed | 5.1 | Premium  |
|------------|--------|-----|----------|
| 2020 00 00 | o.o.u  | 0.1 | . romani |

2 of 2