DesignLights Consortium





| Classification | Premium |
|------------------------|---|
| Primary Use | High-Bay Luminaires for Commercial and Industrial Buildings |
| Reported Input Wattage | 120 W |
| Reported Light Output | 22032 lm |
| Reported CCT | 4000 K |
| Reported CRI (Ra) | 70 |
| Product ID | S-78UYBK |
| DLC Family Code | <u>UUUVFZ</u> |
| Listing Status | Listed |
| Date Qualified | 2023-03-03 |

PRODUCT INFORMATION VIEW DETAILS

| Qualified Product List | Solid State Lighting | | |
|--------------------------------|-----------------------------|--|--|
| Technical Requirements Version | 5.1 | | |
| Product ID | S-78UYBK | | |
| Manufacturer | BIG SHINE LED | | |
| Brand | Big Shine LED | | |
| Model Number | BSL-HB120-SK7-LFLL-4000K-60 | | |
| Parent | No | | |
| Classification | Premium | | |
| DLC Family Code | UUUVFZ | | |
| Input Power Type | AC | | |

PRODUCT CATEGORIZATION VIEW DETAILS

| Category | Indoor Luminaires | |
|-------------------------|---|--|
| General Application | High-Bay | |
| Primary Use Designation | High-Bay Luminaires for Commercial and Industrial Buildings | |

PRODUCT CAPABILITIES VIEW DETAILS

1 of 2 3/8/2023, 2:14 PM

| Integral Controls | Yes | | |
|--|------------------------------------|--|--|
| Dimming Capability and Range | Continuous Dimming to 10% or below | | |
| Integral Control Capability | No Control Capability | | |
| Sensor Type | No Sensor | | |
| SSL V5 Wired Communication Protocol | No Wired Communication Protocol | | |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol | | |
| Field Adjustable Light Output | No | | |
| White-Tunable | No | | |
| Warm-Dimming | No | | |
| Field Adjustable Light Distribution | No | | |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output | 22032 lm |
|-------------------------------|------------|
| Reported Efficacy (AC) | 183.6 lm/W |
| Reported CCT | 4000 K |
| Reported CRI (Ra) | 70 |
| Reported R9 | -35 |
| Reported IES Rf | 74 |
| Reported IES Rg | 94 |
| Reported IES Rcs,h1 | -17 |
| Reported Default Light Output | 22032 lm |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage | 120 W |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 10 % |
| Reported Power Factor | 0.95 |
| Reported Default Input Wattage | 120 W |
| Voltage Range | 100-277 V |

VERSION HISTORY VIEW DETAILS

| 2023-03-03 | Listed | 5.1 | Premium |
|------------|--------|-----|---------|
| 2023-03-02 | Listed | 5.1 | Premium |

2 of 2