DesignLights Consortium



Firefox



| Classification | Standard |
|------------------------|---|
| Primary Use | High-Bay Luminaires for Commercial and Industrial Buildings |
| Reported Input Wattage | 152 W |
| Reported Light Output | 30000 lm |
| Reported CCT | 5000 K |
| Reported CRI (Ra) | 70 |
| Product ID | S-U0N4KV |
| DLC Family Code | UUUVFZ |
| Listing Status | Listed |
| Date Qualified | 2023-03-03 |

PRODUCT INFORMATION VIEW DETAILS

| Qualified Product List | Solid State Lighting | | |
|--------------------------------|------------------------------|--|--|
| Technical Requirements Version | 5.1 | | |
| Product ID | S-U0N4KV | | |
| Manufacturer | BIG SHINE LED | | |
| Brand | Big Shine LED | | |
| Model Number | BSL-HB150-SK7-LFLL-5000K-120 | | |
| Parent | No | | |
| Classification | Standard | | |
| DLC Family Code | UUUVFZ | | |
| Input Power Type | AC | | |

PRODUCT CATEGORIZATION VIEW DETAILS

| Category | Indoor Luminaires | |
|-------------------------|---|--|
| General Application | High-Bay | |
| Primary Use Designation | High-Bay Luminaires for Commercial and Industrial Buildings | |

PRODUCT CAPABILITIES VIEW DETAILS

Integral Controls

| Dimming Capability and Range | Continuous Dimming to 10% or below | | |
|--|------------------------------------|--|--|
| Integral Control Capability | No Control Capability | | |
| Sensor Type | No Sensor | | |
| SSL V5 Wired Communication Protocol | No Wired Communication Protocol | | |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol | | |
| Field Adjustable Light Output | No | | |
| White-Tunable | No | | |
| Warm-Dimming | No | | |
| Field Adjustable Light Distribution | No | | |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output | 30000 lm |
|-------------------------------|----------|
| Reported Efficacy (AC) | 198 lm/W |
| Reported CCT | 5000 K |
| Reported CRI (Ra) | 70 |
| Reported R9 | -35 |
| Reported IES Rf | 74 |
| Reported IES Rg | 94 |
| Reported IES Rcs,h1 | -17 |
| Reported Default Light Output | 28845 lm |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage | 152 W |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 10 % |
| Reported Power Factor | 0.95 |
| Reported Default Input Wattage | 150 W |
| Voltage Range | 100-277 V |

VERSION HISTORY VIEW DETAILS

| 2023-03-03 | Listed | 5.1 | Standard |
|------------|--------|-----|----------|
| 2023-03-02 | Listed | 5.1 | Premium |