# **DesignLights Consortium**





| Classification         | Premium   |
|------------------------|---|
| Primary Use            | High-Bay Luminaires for Commercial and Industrial Buildings |
| Reported Input Wattage | 150 W   |
| Reported Light Output  | 28890 lm  |
| Reported CCT           | 5000 K  |
| Reported CRI (Ra)      | 70  |
| Product ID             | S-M4Y76F  |
| DLC Family Code        | <u>UUUVFZ</u>   |
| Listing Status         | Listed  |
| Date Qualified         | 2023-03-03  |

### **PRODUCT INFORMATION VIEW DETAILS**

| Qualified Product List         | Solid State Lighting        |  |  |
|--------------------------------|-----------------------------|--|--|
| Technical Requirements Version | 5.1                         |  |  |
| Product ID                     | S-M4Y76F                    |  |  |
| Manufacturer                   | BIG SHINE LED               |  |  |
| Brand                          | Big Shine LED               |  |  |
| Model Number                   | BSL-HB150-SK7-LFLL-5000K-60 |  |  |
| Parent                         | No                          |  |  |
| Classification                 | Premium                     |  |  |
| DLC Family Code                | UUUVFZ                      |  |  |
| Input Power Type               | AC                          |  |  |

## **PRODUCT CATEGORIZATION VIEW DETAILS**

| Category                | Indoor Luminaires   |  |
|-------------------------|---|--|
| General Application     | High-Bay  |  |
| Primary Use Designation | High-Bay Luminaires for Commercial and Industrial Buildings |  |

#### PRODUCT CAPABILITIES VIEW DETAILS

1 of 2 3/8/2023, 2:14 PM

| Integral Controls                      | Yes                                |  |  |
|--|------------------------------------|--|--|
| Dimming Capability and Range           | Continuous Dimming to 10% or below |  |  |
| Integral Control Capability            | No Control Capability              |  |  |
| Sensor Type                            | No Sensor                          |  |  |
| SSL V5 Wired Communication Protocol    | No Wired Communication Protocol    |  |  |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol               |  |  |
| Field Adjustable Light Output          | No                                 |  |  |
| White-Tunable                          | No                                 |  |  |
| Warm-Dimming                           | No                                 |  |  |
| Field Adjustable Light Distribution    | No                                 |  |  |

#### REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output         | 28890 lm   |
|-------------------------------|------------|
| Reported Efficacy (AC)        | 192.6 lm/W |
| Reported CCT                  | 5000 K     |
| Reported CRI (Ra)             | 70         |
| Reported R9                   | -35        |
| Reported IES Rf               | 74         |
| Reported IES Rg               | 94         |
| Reported IES Rcs,h1           | -17        |
| Reported Default Light Output | 28890 lm   |

# REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage             | 150 W     |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 10 %      |
| Reported Power Factor              | 0.95      |
| Reported Default Input Wattage     | 150 W     |
| Voltage Range                      | 100-277 V |

#### **VERSION HISTORY VIEW DETAILS**

| 2023-03-03 | Listed | 5.1 | Premium |
|------------|--------|-----|---------|
| 2023-03-02 | Listed | 5.1 | Premium |

2 of 2