DesignLights Consortium





| Classification | Standard |
|------------------------|--|
| Primary Use | Dual Mode Internal Driver (UL Type A and Type B) |
| Reported Input Wattage | 18.3 W |
| Reported Light Output | 2853 lm |
| Reported CCT | 3500 K |
| Reported CRI (Ra) | 83 |
| Product ID | S-VZS8MG |
| DLC Family Code | XXXEUE |
| Listing Status | Listed |
| Date Qualified | 2023-04-10 |

PRODUCT INFORMATION VIEW DETAILS

| Qualified Product List | Solid State Lighting | | |
|--------------------------------|---|--|--|
| Technical Requirements Version | 5.1 | | |
| Product ID | S-VZS8MG | | |
| Manufacturer | BIG SHINE LED | | |
| Brand | Big Shine LED | | |
| Model Number | BSL-TB18-T84-3100K-140-F-T | | |
| Parent | No | | |
| Classification | Standard | | |
| DLC Family Code | XXXEUE | | |
| Length | 4.0 ft | | |
| Input Power Type | AC | | |
| Notes | Dimmable depending on ballast capability. When operated as Type A, dimmable depending on ballast capability | | |

PRODUCT CATEGORIZATION VIEW DETAILS

| Category | Linear Replacement Lamp | |
|-------------------------|--|--|
| General Application | T8 Four-Foot | |
| Primary Use Designation | Dual Mode Internal Driver (UL Type A and Type B) | |

PRODUCT CAPABILITIES VIEW DETAILS

| Integral Controls | No | | |
|--|------------------------------------|--|--|
| Dimming Capability and Range | Continuous Dimming to 10% or below | | |
| Integral Control Capability | No Control Capability | | |
| Sensor Type | No Sensor | | |
| SSL V5 Wired Communication Protocol | No Wired Communication Protocol | | |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol | | |
| Field Adjustable Light Output | No | | |
| White-Tunable | No | | |
| Warm-Dimming | No | | |
| Field Adjustable Light Distribution | No | | |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Beam Angle | 144 ° |
|-------------------------------|----------|
| Reported Light Output | 2853 lm |
| Reported Efficacy (AC) | 156 lm/W |
| Reported CCT | 3500 K |
| Reported CRI (Ra) | 83 |
| Reported R9 | 7 |
| Reported IES Rf | 86 |
| Reported IES Rg | 95 |
| Reported IES Rcs,h1 | -12 |
| Reported Default Light Output | 2853 lm |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage | 18.3 W |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 20 % |
| Reported Power Factor | 0.9 |
| Reported Default Input Wattage | 18.3 W |
| Voltage Range | 100-277 V |

VERSION HISTORY VIEW DETAILS

| 2023-04-10 | Listed | 5.1 | Standard |
|------------|--------|-----|----------|
|------------|--------|-----|----------|