

PANEL 1X4 LED Panel

Big Shine LED's, patented 1x4 panel design is ultra-thin and modern, fitting for any commercial space to replace traditional troffers on a low hanging grid ceiling.

The fixture's edge-light design allows for smooth light transmission. Paired with a silk-printed (LGP), light can distribute evenly. The fixtures heat dissipation technology leads to a longer lifespan.

APPLICATIONS

Commercial

DIMENSIONS



MODEL OPTIONS

Manufacturer	Fixture Type	Wattage	Voltage	Name	Driver	Chip	CCT (X)	Beam Angle (Y)
BSL BIG SHINE LED	PL Panel Light	40W D-Dimming Optional	100-277V	1X4	BS Big Shine Driver	SN San'an	3000K, 4000K, 5000K	110°

TECHNICAL SPECIFICATIONS


	40W
Lumens	5,200
Efficacy	130
CRI	80 (5000K)
Voltage Input	100-277V
Voltage Output	28V
Amperage	0.4
Hertz	50-60 Hz
Total Harmonic Dist.	<15%
Control Options	0-10V Optional (T)
Operating Temp.	-4~122°F
IP Rating	IP20
IK Level	IK06
Weight	7.84 lb
Driver Life	50,000 hrs
L70 Results ¹	>54,000 hrs

¹LM80 and TM21 results are available upon request. Specifications are subject to change without notice.

FIELD & BEAM ANGLES

MODEL	Beam	Height vs. Illuminance (ft vs. lx)		
	Angle	9.8 ft	19.7 ft	29.5 ft
BSL-PL40-1X4-BSSN-5000K-110	110	135.9	34.0	15.1

PHOTOMETRICS



1X4 40W-5000K-110°

MOUNTING OPTIONS

Recessed, Suspended, Flush

STANDARD COLOR OPTIONS

