





US

## Description

With its sleek and modern design, the SAGA LED Area light is an attractive addition to any outdoor space. Whether you're looking to enhance the safety and security of your property or create a welcoming atmosphere for visitors and customers, the SAGA LED Area light delivers reliable and customizable lighting performance that won't disappoint. The SAGA LED Area light also offers exceptional energy efficiency, consuming up to 60% less energy than traditional lighting options. This translates to significant cost savings on your energy bill and reduces your carbon footprint. The power can be adjusted on the field to 25%, 50%, 75% or 100% output.

## Applications

**Building Exteriors** 


# **Specifications - SAGA -LED Area Light**

| Electrical Information             |                                  |  |
|------------------------------------|----------------------------------|--|
| Model No.                          | SGA-300                          |  |
| Power Consumption(±10%)            | 300W                             |  |
| Power Supply                       | LED Driver                       |  |
| Input Voltage                      | 100-277 Vac, 277-480 Vac 50/60Hz |  |
| Power Factor                       | 0.9                              |  |
| Surge Protection                   | 10kV or 20kV SPD options         |  |
| Driver Type                        | Adjustable Power Settings        |  |
| Control                            | 0-10 Dimmable                    |  |
| Optic Information                  |                                  |  |
| LED Type                           | SMD                              |  |
| Luminous Flux (±10%)               | 39646 lm                         |  |
| Efficacy (Minimum CCT @3000K Ra80, | 130 lm/w                         |  |
| Maximum CCT @5000K)                | 130 111/ W                       |  |
| Correlated Color Temperature       | 3000K, 4000K, 5000K (Adjustable) |  |
| Color Rendering Index              | Ra70                             |  |
| Beam Angle                         | Type II, III, IV, V              |  |
| UGR level                          | N/A                              |  |
|                                    |                                  |  |
| Dimensions and Mount               |                                  |  |
| Product Dimension                  | 11.3" x 19" x 2.96"              |  |
| Luminaire Net Weight               | 17.6 lbs (excluding mounts)      |  |
|                                    |                                  |  |

| Luminaire Net Weight | 17.6 lbs (excluding mounts)  |
|----------------------|--|
| Mounting Option      | U-Bracket, Slip-fitter, Rotatable Extruded Arm, Extruded Arm, Trunnion |
| Material             | Aluminum   |
|                      | Polycarbonate Lens   |
| Finish               | Powder Coating   |
| Fixture Color        | Black  |
| IK Rating            | N/A  |
| IP Rating            | IP65   |

|   | Lifespan and Warranty                  |                |
|---|--|----------------|
| I | Operating Temperature                  | -40°F to 122°F |
|   | Warranty                               | 5 Years        |
|   | Safety Certifications                  |                |
| ĺ | Luminaires (UL 1598:2021 Ed.5)         |                |
|   | Luminaires (CSA C22.2#250.0:2021 Ed.5) |                |


### Photometry



### **Mounting Options**

U-Bracket, Slip-fitter, Rotatable Extruded Arm, Extruded Arm, Trunnion

#### Dimensions



Big Shine LED Add: 300 Corporate Blvd, Newburgh, NY 12550 Phone: 845-444-5255