

# SKY X High Bay

Big Shine LED's brilliant Sky X high bay is engineered to powerfully illuminate any facility, delivering light above and below the fixture.

The Sky X is able to create a uniform environment, eliminating dark ceilings.


Sky X has an IP65 rating, which makes it suitable for indoor and semi-outdoor application.

## APPLICATIONS

Industrial, Commercial, Recreational



## DIMENSIONS



## MODEL OPTIONS

Manufacturer	Fixture Type	Wattage	Voltage	Name	Driver	Chip	CCT (X)	Beam Angle (Y)
BSL BIG SHINE LED	HB High Bay	60W, 100W	100-277V	SKX	MW Mean Well	LM Lumileds	3000K, 4000K, 5000K, 5700K	60°, 90°, 120°


## TECHNICAL SPECIFICATIONS

	60W	100W
<b>Lumens</b>	10,380	16,000
<b>Efficacy</b>	174	160
<b>CRI</b>	70 (5000K)	70 (5000K)
<b>Voltage Input</b>	100-277V	100-277V
<b>Amperage</b>	0.5	0.7
<b>Hertz</b>	50-60 Hz	50-60 Hz
<b>THD</b>	15%	15%
<b>Control Options</b>	0-10V Optional	0-10V Optional
<b>Operating Temp.</b>	-40~122°F	-40~122°F
<b>IP Rating</b>	IP40	IP65
<b>IK Level</b>	IK08	IK08
<b>Weight</b>	6.4 lb	6.4 lb
<b>Driver Life</b>	50,000 hrs	50,000 hrs


## FIELD & BEAM ANGLES

MODEL	Beam	Height vs. Illuminance (ft vs. lx)		
	Angle	9.8 ft	19.7 ft	29.5 ft
BSL-HB60-SKX-MWLM-5000K-60	60	1,007.3	251.8	111.9
BSL-HB60-SKX-MWLM-5000K-90	90	599.7	149.9	66.6
BSL-HB60-SKX-MWLM-5000K-120	120	311.2	77.8	34.6
BSL-HB100-SKX-MWLM-5000K-60	60	1,652.1	413.0	183.6
BSL-HB100-SKX-MWLM-5000K-90	90	1,001.5	250.4	111.3
BSL-HB100-SKX-MWLM-5000K-120	120	475.1	118.8	52.8


## PHOTOMETRICS




60W-5000K-60°




60W-5000K-90°




60W-5000K-120°



100W-5000K-60°



100W-5000K-90°



100W-5000K-120°

## MOUNTING OPTIONS

Eye Bolt, Yoke Bracket

## STANDARD COLOR OPTIONS



Black

\*Customized colors available upon RAL request. MOQ applies.

