



### Electrical Information

Model No.	TK4-100	TK4-150	TK4-200	TK4-240
Power Consumption(±10%)	100W	150W	200W	240W
Power Supply	Sosen Driver			
Input Voltage	100-277V/277-480V, 50 / 60 Hz			
Power Factor	>0.95			
Surge Protection	4kV line-line, 4kV line-earth			
Driver Type	Constant Current (CC)			
Control	Continuous Dimming to 10% or below			

### Optic Information

LED Type	LED 3030 Seoul			
Luminous Flux (±5%)	14000lm	21000lm	28000lm	33600lm
Efficacy(4000K Ra80)	140 lm/w			
Correlated Color Temperature	4000K, 5000K			
Color Rendering Index	Ra80			
Beam Angle	H00123/H00124/H00126			
UGR level	<28 (except H00124)			

### Description

Introducing the TK4 LED highbay, the perfect lighting solution for commercial and industrial settings. This high-quality fixture boasts an impressive 140 lm/w efficiency, ensuring bright and clear illumination that will enhance any workspace. One of the standout features of the TK4 is its power adjustable function, allowing you to customize the lighting output to suit your needs. This versatility means you can maximize energy savings while still achieving optimal lighting conditions. The TK4's sturdy aluminum alloy body ensures durability and longevity, while the polycarbonate lens provides excellent light transmission and is resistant to impact and UV damage. This makes the TK4 ideal for use in tough environments where reliability and safety are a top priority.

### Applications

- Industrial and commercial facilities

### Dimensions and Mount

Product Dimension	φ12.4" x7.28"	φ12.4" x7.68"
Luminaire Net Weight	6.61±0.66Lbs	7.5±0.66Lbs
Export Carton Size	13.9" 13.9" 8.5"	
Gross Weight	10.36±0.66 lbs	11±0.66 lbs
Mounting Option	Hook Mount	
Material	Aluminum Alloy Polycarbonate Optical Lens	
Finish	Powder Coating	
Fixture Color	Black	
EPA	N/A	
IK Rating	IK08	
IP Rating	IP65	


### Lifespan and Warranty

Operating Temperature	-22°F to 122°F
Life Time of LED @Ta=25°C	102000hrs-L80 162000hrs-L70
Warranty	5 Years

### Safety Certifications

Luminaire (UL 1598:2021 Ed.5)  
Luminaire (CSA C22.2#250.0:2021 Ed.5)

### Photometry




### Mounting Options

Hook Mount



### Dimensions

100W



150W-240W

