

LED T5 2FT Tube Light


Big Shine LED tubes emit clean, bright, and consistent light. The T5 tubes are designed to be the most energy-efficient solution to replace fluorescent T5 fixtures. They contain no mercury therefore allowing for a brighter and safer space at a lower cost.

Big Shine LED's T5 tubes' single end power meets UL safety standards. With a cover and end caps made of polycarbonate, Big Shine LED tubes are one of the safest options in LED tubes.

Their internal driver provides convenience for every installation and allows them to be safer and more efficient for your facility.



DIMENSIONS



APPLICATIONS

Industrial, Commercial, Recreational

MODEL OPTIONS

| Manufacturer | Fixture Type | Wattage | Voltage | Name | Driver | Chip | CCT | Beam Angle |
|-------------------|---------------|---------|----------|------|----------|----------|---------------------|------------|
| BSL BIG SHINE LED | TL Tube Light | 9W | 100-277V | T52 | LF LiFud | JF Jufei | 3000K, 4000K, 5000K | 120° |


TECHNICAL SPECIFICATIONS

| | 9W |
|----------------------|--------------|
| Lumens | 1,170 |
| Efficacy | 130 |
| CRI | 80 (5000K) |
| Voltage Input | 100-277V |
| Voltage Output | 60-77V |
| Amperage | 0.9 |
| Hertz | 50-60 Hz |
| Total Harmonic Dist. | <20% |
| Control Options | Non-Dimmable |
| Operating Temp. | -4~104°F |
| IP Rating | IP20 |
| IK Level | IK02 |
| Weight | 0.26 lb |
| Driver Life | 50,000 hrs |

FIELD & BEAM ANGLES

| MODEL | Beam | Height vs. Illuminance (ft vs. lx) | | |
|---------------------------|-------|------------------------------------|---------|---------|
| | Angle | 9.8 ft | 19.7 ft | 29.5 ft |
| BSL-TL9-T52-LJF-5000K-120 | 120 | 48.5 | 12.1 | 5.4 |

PHOTOMETRICS



9W-5000K-120°

BASE TYPE

G5, 180° rotating end caps

LENS OPTIONS

