

LED T5 4FT Tube Light


Big Shine LED tubes emit clean, bright, and consistent light. The T5 tubes are designed to be the most energy-efficient solution to replace fluorescent T5 fixtures. They contain no mercury therefore allowing for a brighter and safer space at a lower cost.

Big Shine LED's T5 tubes' single end power meets UL safety standards. With a cover and end caps made of polycarbonate, Big Shine LED tubes are one of the safest options in LED tubes.

Their internal driver provides convenience for every installation and allows them to be safer and more efficient for your facility.



DIMENSIONS



APPLICATIONS

Industrial, Commercial, Recreational

MODEL OPTIONS

Manufacturer	Fixture Type	Wattage	Voltage	Name	Driver	Chip	CCT	Beam Angle
BSL BIG SHINE LED	TL Tube Light	12W	100-277V	T54	LF LiFud	JF Jufei	3000K, 4000K, 4500K, 5000K	120°


TECHNICAL SPECIFICATIONS

	12W
Lumens	1,740
Efficacy	145
CRI	80 (5000K)
Voltage Input	100-277V
Voltage Output	48V
Amperage	0.12
Hertz	50-60 Hz
Total Harmonic Dist.	23%
Control Options	Non-Dimmable
Operating Temp.	-4~104°F
IP Rating	IP20
IK Level	IK02
Weight	0.37 lb
Driver Life	50,000 hrs

FIELD & BEAM ANGLES

MODEL	Beam	Height vs. Illuminance (ft vs. lx)		
	Angle	9.8 ft	19.7 ft	29.5 ft
BSL-TL12-T54-LFJF-5000K-120	120	63.0	15.8	7.0

PHOTOMETRICS




12W-5000K-120°

BASE TYPE

G5, 180° Rotating End Caps

LENS OPTIONS



IP20