

LED T8 4FT Tube Light


Big Shine LED tubes emit clean, bright, and consistent light. The T8 tubes are designed to be the most energy-efficient solution to replace fluorescent T8 and T12 fixtures. They contain no mercury therefore allowing for a brighter and safer space at a lower cost.

Big Shine LED's T8 tubes have a cover and end caps made of polycarbonate, making them one of the safest options in LED tubes. And best of all, they're vibration and impact resistant.

Their internal driver provides convenience for every installation and allows them to be safer and more efficient for your facility.



DIMENSIONS



APPLICATIONS

Industrial, Commercial, Recreational

MODEL OPTIONS

Manufacturer	Fixture Type	Wattage	Voltage	Name	Driver	Chip	CCT	Beam Angle
BSL BIG SHINE LED	TL Tube Light	12W	100-277V	T84	BS Big Shine Driver	SN San'an	3000K, 4000K, 5000K	120°


TECHNICAL SPECIFICATIONS

	12W
Lumens	1,596
Efficacy	133
CRI	80 (5000K)
Voltage Input	100-277V
Voltage Output	36V
Amperage	0.14
Hertz	50-60 Hz
Total Harmonic Dist.	<20%
Control Options	Non-Dimmable
Operating Temp.	-4~104°F
IP Rating	IP20
IK Level	N/A
Weight	0.66 lb
Driver Life	50,000 hrs


FIELD & BEAM ANGLES

MODEL	Beam	Height vs. Illuminance (ft vs. lx)		
	Angle	9.8 ft	19.7 ft	29.5 ft
BSL-TL12-T84-BSSN-5000K-120	120	51.9	13.0	5.8
BSL-TL12-T84-BSSN-4000K-120	120	56.8	14.2	6.3

PHOTOMETRICS



12W-5000K-120°



12W-4000K-120°

BASE TYPE

G13

LENS OPTIONS

