

# CALLISTO II Canopy Light

Big Shine LED's Callisto II is an ideal fixture for dark spaces that need abundant illuminance with little effort. Its striped lens was crafted to create uniform light in tandem with the fixture's wide beam angle.

The Callisto II, built with an aluminum housing, is not only easy to install and operate, but can thrive in damp and dusty environments, indoor and outdoor.


It has versatile application options like gas stations and parking garages.

## APPLICATIONS

Industrial, Commercial, Recreational



## DIMENSIONS



## MODEL OPTIONS

Manufacturer	Fixture Type	Wattage	Voltage	Name	Driver	Chip	CCT	Beam Angle
BSL BIG SHINE LED	CP Canopy	75W, 100W	100-277V	CL2	SO Sosen	PH Philip	4000K, 5000K, 5700K	160°


## TECHNICAL SPECIFICATIONS

	75W	100W
Lumens	8,625	11,500
Efficacy	115	115
CRI	>75 (5000K)	>75 (5000K)
Voltage Input	100-277V	100-277V
Voltage Output	36-48V	36-48V
Amperage	0.8	0.9
Hertz	50-60 Hz	50-60 Hz
Total Harmonic Dist.	<20%	<20%
Control Options	Non-Dimmable	Non-Dimmable
Operating Temp.	4~113°F	4~113°F
IP Rating	IP65	IP65
IK Level	N/A	N/A
Weight	7.94 lb	8.38 lb
Driver Life	50,000 hrs	50,000 hrs


## FIELD & BEAM ANGLES

MODEL	Beam	Height vs. Illuminance (ft vs. lx)		
	Angle	9.8 ft	19.7 ft	29.5 ft
BSL-CP75-CL2-SOPH-4000K-160	160	150.0	37.5	16.7
BSL-CP100-CL2-SOPH-4000K-160	160	196.2	49.0	21.8

## PHOTOMETRICS



75W-4000K-160°



100W-4000K-160°

## MOUNTING OPTIONS

Flush, Recessed

## STANDARD COLOR OPTIONS

