

Catalog Number	
Notes	
Type	

TECHNICAL SPECIFICATIONS

Model No.	PLD2-18*	PLD2-25
Power Consumption(±10%)	18W	24W/25W (Up/Down)
Power Supply	LED Driver	
Input Voltage	120-277V, 50/60 Hz	
Power Factor	0.8	
Surge Protection	L-N: 2.5kV, L-N-PE: 2.5kV	
Driver Type	Constant Current (CC)	
Control	0-10V Dimmable	

OPTIC SPECIFICATIONS

LED Type	SMD	
Luminous Flux (±10%)	2070 lm	2875 lm
Efficacy(4000K Ra80)	115 lm/w	115 lm/w
Correlated Color Temperature	3000K, 4000K, 5000K (Adjustable)	
Color Rendering Index	Ra80	
Beam Angle Up/Down	110°	110°/110°
UGR level	N/A	

MOUNTING AND PRODUCT DIMENSIONS

Product Dimension	23.7" x 2.25" x 3"
Luminaire Net Weight	4.41 lbs
Export Carton Size	72.5 x 26 x 44
Gross Weight	26.45 lbs
Mounting Option	Suspended, Flushed, and Surface Mounting
Material	Die-cast Aluminum
Finish	Polycarbonate
Fixture Color	Powder Coating
IK Rating	White
IP Rating	N/A

DESCRIPTION

Introducing our revolutionary 2ft Linear Luminaire with Up/Down Light, designed to elevate your lighting experience in a compact form factor. This exceptional fixture seamlessly combines ambient and accent lighting, delivering a perfect balance of functionality and aesthetics. The innovative design of this luminaire ensures that light is emitted in both upward and downward directions, creating a harmonious illumination that enhances any space. Whether you're looking to create a cozy ambiance or highlight architectural elements, this luminaire excels in providing outstanding performance. Measuring at a convenient 2ft length, this linear fixture offers optimal coverage while maintaining a sleek and compact profile.

*The 18W option does not offer up light.

APPLICATION(S)

Offices
Retail Spaces
Hospitality Venues



LIFESPAN AND WARRANTY

Operating Temperature	-4°F to 113°F
Warranty	5 Years

SAFETY CERTIFICATIONS

Luminaires (UL 1598:2021 Ed.5)
Luminaires (CSA C22.2#250.0:2021 Ed.5)




PHOTOMETRY



MOUNTING OPTIONS

Suspended Mounting
Flush Mounting
Surface Mounting

Corner, 3-way, and 4-way line connectors are available to link luminaries.



Series	Wattage & Lumen Output	Voltage	Corelated Color Temperature (CCT)	Beam Angle	Control Options
PLD2 (Pleiades II 2FT)	18W (2070lm) 25W (2875lm)	MV (120-277V)	30K (3000K) 40K (4000K) 50K (5000K)	110B (110°)	0-10V (Dimmable)

Mounting Option	Finish Color	Accessories
SSM (Suspended Mounting) FM (Flush Mounting) SM (Surface Mounting)	WH (White)	EMB (Battery Back-up) 1C (Corner Connector) 3W-C (3-Way Connector) 4W-C (4-Way Connector)